

TRUCKSTAR PRO

Brightest OSRAM truck light



Excellent brightness

More light allows to see farther and therefore react sooner



More than double the service life

Reduced downtime and fleet costs compared to standard lamps



Very high vibration resistance

Suitable for heavy duty applications



The most powerful halogen truck light from OSRAM

Discover TRUCKSTAR PRO signal lamps - the brightest truck light from OSRAM with excellent value for money. With up to 100% more light than standard lamps, extremely long life and very high vibration resistance these 24 volt lamps are ideal for professional drivers while reducing downtime and fleet costs. Thanks to the high vibration resistance, TRUCKSTAR PRO lamps are suitable even for heavy duty applications. Due to their impressive brightness and more than double the service life compared to standard lamps, the lamps improve your safety while driving on the road.

Product family datasheet

Technical data

	Product information	General Product Information	Electrical Data		
Product description	Application (Category and Product specific)	Global order reference	Power input	Nominal voltage	Nominal wattage
TRUCKSTAR PRO P21/5W	Auxiliary lamp	7537TSP	28 / 10 W	24.0 V	21/5 W
TRUCKSTAR PRO W5W	Auxiliary lamp	2845TSP	7 W	24.0 V	5 W
TRUCKSTAR PRO R10W	Auxiliary lamp	5637TSP	12.5 W	24.0 V	10 W
TRUCKSTAR PRO R5W	Auxiliary lamp	5627TSP	7 W	24.0 V	5 W
TRUCKSTAR PRO T4W	Auxiliary lamp	3930TSP	5 W	24.0 V	4 W

			Photometric Data		Physical Attributes & Dimensions
Product description	Power input tolerance	Test voltage	Nominal luminous flux	Luminous flux tolerance	Lamp base
TRUCKSTAR PRO P21/5W	±6 / ±10 %	28.0 V	440/40 lm	±15 / ±20 %	BAY15d
TRUCKSTAR PRO W5W	±10 %	28.0 V	50 lm	±20 %	W2.1x9.5d
TRUCKSTAR PRO R10W	±10 %	28.0 V	125 lm	±20 %	BA15s
TRUCKSTAR PRO R5W	±10 %	28.0 V	50 lm	±20 %	BA15s
TRUCKSTAR PRO T4W	±10 %	28.0 V	35 lm	±20 %	BA9s

			Lifetime Data		Capabilities	Certificates & standards
Product description	Length	Diameter	Lifespan B3	Lifespan Tc	Technology	ECE category
TRUCKSTAR PRO P21/5W	52.5 mm	25.0 mm	100 / 1000 hr	200 / 2000 hr	AUX	P21/5W
TRUCKSTAR PRO W5W	26.8 mm	10.0 mm	1000 hr	4000 hr	AUX	W5W
TRUCKSTAR PRO R10W	37.5 mm	16.0 mm	1000 hr	2000 hr	AUX	R10W
TRUCKSTAR PRO R5W	37.5 mm	16.0 mm	500 hr	1000 hr	AUX	R5W
TRUCKSTAR PRO T4W	27.4 mm	9 mm	550 hr	1000 hr	AUX	T4W

	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Primary article identifier	Candidate list substance 1	Declaration no. in SCIP database
TRUCKSTAR PRO P21/5W	4008321798138 4062172158480 4052899423695 4062172121132	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO W5W	4052899560543 4008321798077 4062172158305	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO R10W	4062172158398 4008321821232	No declarable substances contained	No declarable substances contained

Product family datasheet

Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
Product description	Primary article identifier	Candidate list substance 1	Declaration no. in SCIP database
TRUCKSTAR PRO R5W	4062172158367 4008321821201	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO T4W	4062172158336 4008321795106 4008321174055 4008321842589	No declarable substances contained	No declarable substances contained

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

