## **OSRAM**

# **LEDriving SL P13W**

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P13W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for P13W

LEDriving SL P13W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P13W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Product family datasheet

#### Technical data

|                     | Product information                           |  | General Product<br>Information | Electrical Data |                 |
|---------------------|---|--|--------------------------------|-----------------|-----------------|
| Product description | Product<br>type (off-<br>road vs.<br>on-road) | Application (Category and Product specific)        | Global order reference         | Power<br>input  | Nominal voltage |
| LEDriving SL ≜ P13W | Off-road ≙<br>P13W                            | Mainly used for daytime running light applications | 828DWP                         | 1.90 W          | 12.0 V          |

|                     |                 |                                 |                 | Photometric Data      | Physical Attributes & Dimensions |
|---------------------|-----------------|---------------------------------|-----------------|-----------------------|----------------------------------|
| Product description | Nominal wattage | Power<br>input<br>toleranc<br>e | Test<br>voltage | Nominal luminous flux | Lamp base                        |
| LEDriving SL ≜ P13W | 1 W             | ±10 %                           | 13.5 V          | 130 lm                | PG18.5d-1                        |

|                     |         |          | Lifetime D     | ata            | Capabilities |
|---------------------|---------|----------|----------------|----------------|--------------|
| Product description | Length  | Diameter | Lifespan<br>B3 | Lifespan<br>Tc | Technology   |
| LEDriving SL ≙ P13W | 48.3 mm | 23.0 mm  | 1500 hr        | 4000 hr        | LED 1)       |

| Environmental & Regulatory Information                                |
|---|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |

|                     | mornation according to 35 of 20 regulation (22) 2505/2000 (REXCIT) |                            |                      |  |  |
|---------------------|--|----------------------------|----------------------|--|--|
| Product description | Primary article identifier   | Candidate list substance 1 | CAS No. of substance | Safe use instruction   |  |
| LEDriving SL ≜ P13W | 4062172401432  <br>4062172150279                                   | Lead                       | 7439-92-1            | The identification of the Candidate List substance is sufficient to allow safe use of the article. |  |

| Product description | Declaration no. in SCIP database |  |
|---------------------|----------------------------------|--|
| LEDriving SL ≙ P13W | 86a80c4c-80ba-                   |  |
|                     | 4d88-b8fd-                       |  |
|                     | 60cafbfef775                     |  |

 $<sup>^{1)}</sup>$  Light-emitting diode lamp

#### Product family datasheet

#### Download Data

#### File



**Brochures** 

LEDriving Retrofits - Exchange overview (EN)

#### Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.