## **OSRAM**

# LEDriving HL INTENSE H4/H19





Up to +350% more brightness

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner.Compared to minimum ECE R112



Very compact LED replacement for conventional H4H19 high and low beam lamps (2in1) Reduced glaring thanks to an

optimized light distribution



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



5-year OSRAM guarantee

For precise conditions, please refer to www.osram.com/amguarantee





#### OSRAM's highest performing LED off-road retrofit lamp

With up to +350% more brightness (compared to ECE R112) and a very compact LED replacement of conventional H7/H18 and H4/H19 high and low beam lamps, the LEDriving HL INTENSE is OSRAM's highest performing LED off-road retrofit lamp ever! This LED retrofit lamp offers OSRAM top technology beam pattern as well as an easy installation with a wide OSRAM range of suitable accessories. Top thermal management technology with integrated active cooling - a high speed fan ensures maximized heat dissipation for more powerful performances. Also premium OSRAM quality, manufactured in a certified OSRAM production plant in Italy, and a 5-year guarantee as well as a long service life. For precise guarantee conditions please refer to www.osram.com/am-guarantee.The LED high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a color temperature of 6,000K. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for an even wider range of car models. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Technical data

	Product in	formation		General Produ Information	ct El	ectrical D	Pata
Product description	Application (Category and Product specific)		Product type (off- road vs. on-road)	Global order reference		ower put	Nominal voltage
LEDriving HL INTENSE ≜ H4/H19	Mainly used for Low Beam, High Beam		Off-road ≙ H4/H19	64193DWINT		25 / 12.0 V 21.0 W	
				Photometric Da	ta		Physical Attributes & Dimensions
Dreduct description	Nominal wattage		Test	Nominal lumino	ue Lur	ninous	Diameter
Product description	Nominal v	vattage	voltage	flux	flux		Dameter
LEDriving HL INTENSE = H4/H19	27 W	vattage			flux	k erance	18.5 mm
		Capabilities	voltage 13.2 V Environm Informati	flux	flux tole ±20 ory Informati . 33 of EU	erance	
	27 W	-	voltage 13.2 V Environm Informati Regulatio	flux 1900/1350 lm nental & Regulato ion according Art. on (EC) 1907/200 article D	flux tole ±20 ory Informati . 33 of EU	k erance ) % ion o. in	

\_\_\_\_

### Download Data

	File
$\mathbf{z}$	User instruction LEDriving HL INTENSE
Z	Brochures LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.









