OSRAM

LEDriving HL BRIGHT HB4/HIR2



Up to +300% more brightness

More light allows to see

farther and therefore react

sooner. Signs, obstacles and

hazards can be recognized sooner. Compared to minimum ECE R112, for H7/H18 & H4/H19



Very compact LED replacement for conventional HB4HIR2 high and low beam lamps

Reduced glaring thanks to an optimized light distribution



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



4 year OSRAM guarantee

For precise conditions, please refer to www.osram.com/amguarantee





High-performing LED retrofit lamp providing improved visibility and a stylish look

With up to +300% more brightness (compared to ECE R112, for H7/H18 & H4/H19), the OSRAM LEDriving HL BRIGHT retrofit lamp ensures optimum visibility and thus allowing drivers to recognize signs, obstacles and hazards sooner than conventional lamps. This LED retrofit lamp not only creates a stylish modern look with a cool white color temperature of 6,000K but also offers reduced glaring thanks to an optimized light distribution. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to ECE R112) and better visibility thanks to daylight effect. The pair of lamps comes with a 4-year OSRAM guarantee. For precise quarantee conditions please refer to www.osram.com/am-guarantee.The LEDriving HL BRIGHT high and low beam lamps by OSRAM replace conventional halogen lamps and are 12V compatible. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product information		General Informa			Electrical Data		
Product description	Application (Category and Product specific)		Product type (off- road vs. on-road)	Global order reference		Power input	-	
LEDriving HL BRIGHT ≜ HB4/HIR2	Mainly used for Low Beam, High Beam and Fog light applications		Off-road ≙ HB4/HIR2	9006DWBRT		19 W	W 12.0 V	
			Photometric Data			Physical Attributes & Dimensions		Lifetime Data
Product description	Nominal wattage		Nominal luminous flux		Luminous flux tolerance	Diamet	er	Lifespan Tc
LEDriving HL BRIGHT ≙ HB4/HIR2	19 W		1900 lm		±20 %	14.0 mr	n	5000 hr
LEDriving HL BRIGHT ≜ HB4/HIR2	19 W Capabilities	Informa	1900 lm nmental & Reg ation according tion (EC) 1907,	Art. 33 of	ormation EU	14.0 mr	n	5000 hr
LEDriving HL BRIGHT	1 1	Informa Regulat	nmental & Reg ation according tion (EC) 1907, y article	Art. 33 of /2006 (RE/	ormation EU ACh) tion no. in	14.0 mr	n	5000 hr

Product family datasheet

Download Data

File



User instruction LEDriving HL BRIGHT



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















